# **MARS Pressure Switches & Heat Pump Thermostats**

## **Condenser Fan Cycling Switches**

Fan cycling switches provide refrigeration and air conditioning from low ambient conditions.

### Specifications:

- Contacts rated at 6 amps, 24-240 volts
- 1/4" female flare S.A.E. mounting
- 18" leads

#### Features:

- · Tamper proof construction
- · Direct mounting on tubing
- · UL & CSA recognized



| MARS<br>NO. | OPENING<br>PRESSURE | RESET<br>PRESSURE | NOTES                              |
|-------------|---------------------|-------------------|------------------------------------|
| 43301       | 75                  | 100               | 1/4" Female Flare S.A.E. Mounting  |
| 43302       | 110                 | 170               | 1/4" Female Flare S.A.E. Mounting  |
| 43303       | 125                 | 265               | 1/4" Female Flare S.A.E. Mounting  |
| 43304       | 150                 | 225               | 1/4" Female Flare S.A.E. Mounting  |
| 43305       | 190                 | 275               | 1/4" Female Flare S.A.E. Mounting  |
| 43370       | 180                 | 240               | 1/4" Female Flare, S.A.E. Mounting |
| 43306       | 210                 | 275               | 1/4" Female Flare S.A.E. Mounting  |
| 43307       | 300                 | 400               | 1/4" Female Flare S.A.E. Mounting  |

# Manual Reset - High Pressure Cut Out Open on Pressure Rise



43301

| MARS<br>NO. | OPENING<br>PRESSURE | RESET<br>PRESSURE | NOTES                             |
|-------------|---------------------|-------------------|-----------------------------------|
| 43312       | 375                 | Manual            | 1/4" Female Flare S.A.E. Mounting |
| 43313       | 410                 | Manual            | 1/4" Female Flare S.A.E. Mounting |
| 43314       | 415                 | Manual            | Capilllary Tube                   |
| 43315       | 440                 | Manual            | Capilllary Tube                   |
| 43316       | 475                 | Manual            | 1/4" Female Flare S.A.E. Mounting |
| 43368       | 590                 | Manual            | 1/4" Female Flare w/snubber       |
| 43369       | 610                 | Manual            | 1/4" Female Flare w/snubber       |

### **Heat Pump Defrost Thermostats**

MARS heat pump defrost thermostats are designed for direct replacement of most existing controls of this type. The temperature settings and tubing sizes have been carefully selected from the most popular OEM settings. Each MARS thermostat comes complete with extra long 54 inch leads, mounting clamp, and installation instructions for fast and simple field installation.



### Features:

- Four controls cover most requirements
- · Tapered mounting edge for maximum heat transfer
- · Extra long 54 inch leads for simple wiring
- · Individually boxed with mounting clamp and instructions
- · UL & CUL listed

### **Electrical Ratings:**

| Cycles<br>X1000 | Volts  | FLA  | LRA  | Resistive<br>Amps | VA  |
|-----------------|--------|------|------|-------------------|-----|
| 100             | 120VAC | 5.8  | 34.8 | 10                | 125 |
| 100             | 240VAC | 2.9  | 17.4 | 10                | 125 |
| 30              | 120VAC | 10.0 | 40.0 | -                 | -   |
| 30              | 240VAC | 10.0 | 40.0 | -                 | _   |
| 100             | 30VDC  | -    | -    | 1                 | _   |

| MARS<br>NO. | OPERATING TEMPERATURES F° |       | TUBE MOUNTING IN | LEADS IN   |
|-------------|---------------------------|-------|------------------|------------|
|             | OPEN                      | CLOSE | TOBE MODITING IN | LEFTEO III |
| 33490       | 80                        | 30    | 3/8              | 54         |
| 33492       | 80                        | 30    | 1/2              | 54         |
| 33494       | 65                        | 30    | 3/8              | 54         |
| 33496       | 65                        | 30    | 1/2              | 54         |