


Technical data and ordering

MT/MTZ -Medium/High Temperature Reciprocating Compressors



Nominal capacity (Btu/h) ²			Connection type Rotolock (in.)	Connection with supplied sleeve (in. ODF)	No. of cylinders	Weight (lbs.)	208–230/1/60		200–230/3/60		460/3/60	
R-22 ³	R-134a ³	R-404A ⁴ R-507A ⁴					Danfoss Model No. ¹	Danfoss Code No.	Danfoss Model No. ¹	Danfoss Code No.	Danfoss Model No. ¹	Danfoss Code No.
15903			1 × 1	½ × ¾	1	46	MT18JA1*VE	MT18-1VI	MT18JA3*VE	MT18-3VI	MT18JA4*VE	MT18-4VI
21975			1 × 1 ⁽⁵⁾	½ × ¾ ⁽⁵⁾	1	46	MT22JC1*VE	MT22-1VI⁵	MT22JC3*VE	MT22-3VI	MT22JC4*VE	MT22-4VI
30231			1 × 1 ⁽⁵⁾	½ × ¾ ⁽⁵⁾	1	51	MT28JE1*VE	MT28-1VI⁵	MT28JE3*VE	MT28-3VI	MT28JE4*VE	MT28-4VI
33044			1 ¼ × 1	¾ × ½	1	53	MT32JF1*VE	MT32-1VI	MT32JF3*VE	MT32-3VI	MT32JF4*VE	MT32-4VI
37992			1 ¼ × 1	¾ × ½	1	55	MT36JG1*VE	MT36-1VI	MT36JG3*VE	MT36-3VI	MT36JG4*VE	MT36-4VI
42930			1 ¼ × 1	¾ × ½	1	57	MT40JH1*VE	MT40-1VI	MT40JH3*VE	MT40-3VI	MT40JH4*VE	MT40-4VI
43999			1 ¾ × 1 ¼	¾ × ¾	2	82	MT44HJ1*VE	MT44-1VI	MT44HJ3*VE	MT44-3VI	MT44HJ4*VE	MT44-4VI
50160			1 ¾ × 1 ¼	¾ × ¾	2	82	MT50HK1*VE	MT50-1VI	MT50HK3*VE	MT50-3VI	MT50HK4*VE	MT50-4VI
56420			1 ¾ × 1 ¼	¾ × ¾	2	86	MT56HL1*VE	MT56-1VI	MT56HL3*VE	MT56-3VI	MT56HL4*VE	MT56-4VI
64366			1 ¾ × 1 ¼	¾ × ¾	2	86	MT64HM1*VE	MT64-1VI	MT64HM3*VE	MT64-3VI	MT64HM4*VE	MT64-4VI
74561			1 ¾ × 1 ¼	¾ × ¾	2	88			MT72HN3*VE	MT72-3VI	MT72HN4*VE	MT72-4VI
84977			1 ¾ × 1 ¼	1 ⅛ × ¾	2	88			MT80HP3*VE	MT80-3VI	MT80HP4*VE	MT80-4VI
95898			1 ¾ × 1 ¼	1 ⅛ × ¾	4	132			MT100HS3*VE	MT100-3VI	MT100HS4*VE	MT100-4VI
124678			1 ¾ × 1 ¼	1 ⅛ × ¾	4	141			MT125HU3*VE	MT125-3VI	MT125HU4*VE	MT125-4VI
140697			1 ¾ × 1 ¼	1 ⅛ × ¾	4	148			MT144HV3*VE	MT144-3VI	MT144HV4*VE	MT144-4VI
156820			1 ¾ × 1 ¼	1 ⅛ × ¾	4	152			MT160HW3*VE	MT160-3VI	MT160HW4*VE	MT160-4VI
11200	8980		1 × 1	½ × ¾	1	46	MTZ18JA1*VE	MTZ18-1VI	MTZ18JA3*VE	MTZ18-3VI	MTZ18JA4*VE	MTZ18-4VI
	14849	12306	1 × 1 ⁽⁵⁾	½ × ¾ ⁽⁵⁾	1	46	MTZ22JC1*VE	MTZ22-1VI⁵	MTZ22JC3*VE	MTZ22-3VI	MTZ22JC4*VE	MTZ22-4VI
	19276	15986	1 × 1 ⁽⁵⁾	½ × ¾ ⁽⁵⁾	1	51	MTZ28JE1*VE	MTZ28-1VI⁵	MTZ28JE3*VE	MTZ28-3VI	MTZ28JE4*VE	MTZ28-4VI
	20949	17480	1 ¼ × 1	¾ × ½	1	53	MTZ32JF1*VE	MTZ32-1VI	MTZ32JF3*VE	MTZ32-3VI	MTZ32JF4*VE	MTZ32-4VI
	24482	20189	1 ¼ × 1	¾ × ½	1	55	MTZ36JG1*VE	MTZ36-1VI	MTZ36JG3*VE	MTZ36-3VI	MTZ36JG4*VE	MTZ36-4VI
	27864	23031	1 ¼ × 1	¾ × ½	1	57	MTZ40JH1*VE	MTZ40-1VI	MTZ40JH3*VE	MTZ40-3VI	MTZ40JH4*VE	MTZ40-4VI
	30110	24323	1 ¾ × 1 ¼	¾ × ¾	2	82	MTZ44HJ1*VE	MTZ44-1VI	MTZ44HJ3*VE	MTZ44-3VI	MTZ44HJ4*VE	MTZ44-4VI
	34538	28590	1 ¾ × 1 ¼	¾ × ¾	2	82	MTZ50HK1*VE	MTZ50-1VI	MTZ50HK3*VE	MTZ50-3VI	MTZ50HK4*VE	MTZ50-4VI
	38881	32451	1 ¾ × 1 ¼	¾ × ¾	2	86					MTZ56HL4*VE	MTZ56-4VI
	44404	36056	1 ¾ × 1 ¼	¾ × ¾	2	86	MTZ64HM1*VE	MTZ64-1VI	MTZ64HM3*VE	MTZ64-3VI	MTZ64HM4*VE	MTZ64-4VI
	50000	40894	1 ¾ × 1 ¼	¾ × ¾	2	88			MTZ72HN3*VE	MTZ72-3VI	MTZ72HN4*VE	MTZ72-4VI
	56336	46521	1 ¾ × 1 ¼	1 ⅛ × ¾	2	88			MTZ80HP3*VE	MTZ80-3VI	MTZ80HP4*VE	MTZ80-4VI
	63963	52953	1 ¾ × 1 ¼	1 ⅛ × ¾	4	132			MTZ100HS3*VE	MTZ100-3VI	MTZ100HS4*VE	MTZ100-4VI
	78906	68297	1 ¾ × 1 ¼	1 ⅛ × ¾	4	141			MTZ125HU3*VE	MTZ125-3VI	MTZ125HU4*VE	MTZ125-4VI
	96936	80472	1 ¾ × 1 ¼	1 ⅛ × ¾	4	148			MTZ144HV3*VE	MTZ144-3VI	MTZ144HV4*VE	MTZ144-4VI
	107631	87421	1 ¾ × 1 ¼	1 ⅛ × ¾	4	152			MTZ160HW3*VE	MTZ160-3VI	MTZ160HW4*VE	MTZ160-4VI

¹These compressor models have threaded sight glass and ¾ in. flare oil equalization line.

²To determine the nominal capacity for R-407A/C/F, R-452A, R-448A, R-449A, check Coolselector.

³Evaporator temperature = 45 °F, condensing temperature = 130 °F, superheat = 20 °F, subcooling = 15 °F

⁴Evaporator temperature = 20 °F, condensing temperature = 120 °F, superheat = 20 °F, subcooling = 0 °F

⁵Actual connection for MT and MTZ 22–28 (208–230/1/60) is rotolock 1 ¼ in. × 1 in. and connection with supplied sleeve is ¾ in. × ½ in. ODF. Capacitor values and relays for 1 phase compressors are available on page 80.