

SPLIT AIR CONDITIONER SYSTEM

RSA14 FEATURES

- R410A chlorine-free refrigerant
- Energy-efficient compressor
- Internal protection against high temperature motor overload conditions
- High quality condenser with inner-groove copper tube and aluminum fin
- 45° Service valves with sweat connections and easy-access gauge ports
- Factory-installed high pressure switch and low pressure switch
- AHRI certified and ETL listed
- Compact design, easy installation and transportation
- Powder-coated galvanized steel cabinet
- Wire fan discharge grille
- Steel louver coil guard



RSA14 SPECS AT A GLANCE

Model	Tonnage	Sound Power (dB)	Dimensions (in.) (H x W x D)
RSA1418S1A	1.5	69	24-15/16 x 23-5/8 x 23-5/8
RSA1424S1A	2.0	72	24-15/16 x 23-5/8 x 23-5/8
RSA1430S1A	2.5	75	24-15/16 x 28 x 28
RSA1436S1A	3.0	76	24-15/16 x 29-1/8 x 29-1/8
RSA1442S1A	3.5	77	33-3/16 x 28 x 28
RSA1448S1A	4.0	78	33-3/16 x 28 x 28
RSA1460S1A	5.0	81	33-3/16 x 29-1/8 x 29-1/8



**You can count on
Century for Comfort.**

SPLIT AIR CONDITIONER SYSTEM

RSA15 FEATURES

- R410A chlorine-free refrigerant
- Energy-efficient compressor
- Internal protection against high temperature motor overload conditions
- High quality condenser with inner-groove copper tube and aluminum fin
- 45° Service valves with sweat connections and easy-access gauge ports
- Factory-installed high pressure switch and low pressure switch
- AHRI certified and ETL listed
- Compact design, easy installation and transportation
- Powder-coated galvanized steel cabinet
- Wire fan discharge grille
- Steel louver coil guard



RSA15 SPECS AT A GLANCE

Model	Tonnage	Sound Power (dB)	Dimensions (in.) (H x W x D)
RSA1518S1A	1.5	70	24-15/16 x 23-5/8 x 23-5/8
RSA1524S1A	2.0	73	24-15/16 x 28 x 28
RSA1530S1A	2.5	72	24-15/16 x 28 x 28
RSA1536S1A	3.0	75	24-15/16 x 29-1/8 x 29-1/8
RSA1542S1A	3.5	75	33-3/16 x 29-1/8 x 29-1/8
RSA1548S1A	4.0	76	33-3/16 x 29-1/8 x 29-1/8
RSA1560S1A	5.0	77	33-3/16 x 29-1/8 x 29-1/8

