



1900 Wellworth Ave. • Jackson, MI 49203
517-787-2100

Submittal Data

MODEL
PTHP09A130B

Project Name:	
Location:	
Engineer:	
Submitted to:	
Submitted by:	

Approval:	
Date:	
Construction:	
Unit #:	
Drawing #:	

Reference:

PERFORMANCE DATA

Power supply 208/230V/60

Cooling

Capacity	Btu/h	9300/9500
Input	W	795/835
Rated current	A	3.9/3.7
EER	Btu/w	11.7/11.4

Heating

Capacity	Btu/h	8300/8500
Rated Input (elect. Heater)	Kw	3
Rated current	A	3.3/3.1
Max. Current	A	5.1

Compressor Electrical

Model	39B202A
Type	ROTARY
Brand	RECHI
Capacitor	mF 25
Refrigerant type	oz R410A/32.8

Air flow & Noise level


Indoor air flow	CFM	410/365
Indoor noise level	dB(A)	45/35
Outdoor noise level	dB(A)	66

Indoor Fan Motor

Model	YDK-25-4P2
Input	W 55
Capacitor	uF 1.5
Speed(Hi/Lo)	rpm 750/650

Accessories

Wall Sleeve-breakdown	7602-500F
Stamped Aluminum Grill	7602-501F
Architectural Aluminum Grill	7602-505F
Colored Polymer Grills	See Catalog
Indoor Discharge Air Deflector	7602-508F
Wireless Wall Thermostat	7602-536
Universal Remote	7602-512



Outdoor Fan Motor

Model	YDK-55-4P2
Input	W 95
Speed	RPM 1600

Dimensional Data


Dimension(W*D*H)	inch	41.97x21.1x16.1
Packing (W*D*H)	inch	45.3x24.8x18.9
Net/Gross weight	lbs.	104/117

System Data

Design pressure	PSIG
Thermostat type	Remote Controller On-Board Wired Thermostat

Cord and Plug

Cord Length	ft.	6.5
Plug Face	Nema	6-20P



Subbase (no receptical)	7602-509F
Drain Kit	7602-506F
Duct Kit	7602-511F
Wired Thermostat	7800-201
Thermostat Locking Cover	7602-535