



1900 Wellworth Ave. • Jackson, MI 49203
517-787-2100

Submittal Data

MODEL
PTHP12A230BSC

Project Name:	
Location:	
Engineer:	
Submitted to:	
Submitted by:	

Approval:	
Date:	
Construction:	
Unit #:	
Drawing #:	

Reference:

PERFORMANCE DATA

Power supply 265V/1PH/60Hz

Cooling

Capacity	Btu/h	12000
Input	W	1155
Rated current	A	4.35
EER	Btu/w	10.4

Heating

Capacity	Btu/h	11000
Rated Input (elect. Heater)	Kw	3
Rated current	A	3.88
Max. Current	A	5.1

Compressor Electrical

Model	44A287A
Type	ROTARY
Brand	Richi
Capacitor	mF 30
Refrigerant type	oz R410A/27.5

Air flow & Noise level

Indoor air flow	CFM	405/333
Indoor noise level	dB(A)	44/36
Outdoor noise level	dB(A)	68

Indoor Fan Motor

Model	YDK-25-4P2-1
Input	W 55
Capacitor	uF 1
Speed(Hi/Lo)	rpm 830/600

Accessories

Wall Sleeve-breakdown	7602-500F		
Stamped Aluminum Grill	7602-501F		
Architectural Aluminum Grill	7602-505F	Subbase (no receptical)	7602-509F
Colored Polymer Grills	See Catalog	Drain Kit	7602-506F
Indoor Discharge Air Deflector	7602-508F	Duct Kit	7602-511F
Wireless Wall Thermostat	7602-536	Wired Thermostat	7800-200
Universal Remote	7602-512	Thermostat Locking Cover	7602-535



Outdoor Coil Seacoast Coating

Outdoor Fan Motor

Model	YDK-45-4P2
Input	W 135
Speed	RPM 1600

Dimensional Data

Dimension(W*D*H)	inch	41.97x21.1x16.1
Packing (W*D*H)	inch	45.3x24.8x18.9
Net/Gross weight	lbs.	110/123

System Data

Design pressure	PSIG
	Remote Controller
Thermostat type	On-Board
	Wired Thermostat

Cord and Plug

Hard Wire Only