



1900 Wellworth Ave. • Jackson, MI 49203
517-787-2100

Submittal Data

MODEL
PTHP15A250BSC

Project Name:	
Location:	
Engineer:	
Submitted to:	
Submitted by:	

Approval:	
Date:	
Construction:	
Unit #:	
Drawing #:	

Reference:

PERFORMANCE DATA

Power supply 265V/1PH/60Hz

Cooling

Capacity	Btu/h	15000
Input	W	1560
Rated current	A	5.88
EER	Btu/w	9.61

Heating

Capacity	Btu/h	14000
Rated Input (elect. Heater)	Kw	5
Rated current	A	5.18
Max. Current	A	7.7

Compressor Electrical

Model	50A367Q
Type	ROTARY
Brand	Richi
Capacitor	mF 25
Refrigerant type	oz R410A/33.5

Air flow & Noise level

Indoor air flow	CFM	405/333
Indoor noise level	dB(A)	44/36
Outdoor noise level	dB(A)	68

Indoor Fan Motor

Model	YDK-30-4P2-1
Input	W 64
Capacitor	uF 1
Speed(Hi/Lo)	rpm 970/800

Accessories

Wall Sleeve-breakdown	7602-500F		
Stamped Aluminum Grill	7602-501F		
Architectural Aluminum Grill	7602-505F	Subbase (no receptical)	7602-509F
Colored Polymer Grills	See Catalog	Drain Kit	7602-506F
Indoor Discharge Air Deflector	7602-508F	Duct Kit	7602-511F
Wireless Wall Thermostat	7602-536	Wired Thermostat	7800-200
Universal Remote	7602-512	Thermostat Locking Cover	7602-535



Outdoor Coil Seacoast Coating

Outdoor Fan Motor

Model	YDK-45-4P2
Input	W 135
Speed	RPM 1600

Dimensional Data

Dimension(W*D*H)	inch	41.97x21.1x16.1
Packing (W*D*H)	inch	45.3x24.8x18.9
Net/Gross weight	lbs.	112/126

System Data

Design pressure	PSIG
	Remote Controller
Thermostat type	On-Board
	Wired Thermostat

Cord and Plug

Hard Wire Only