

# Technical data and ordering

## KPU 19 Thermostats



KPU Series	Bulb type	Range (°F)	Contact/Reset	Capillary tube length (in.)	Maximum bulb temperature (°F)	Competitor part no.	Danfoss Type	Danfoss Code No.
KPU 19	Remote bulb	-30 to 80	SPDT/Auto	120	140	A19ABC-24C A19ABC-37C A19ABC-74C A19AAC-4C A19AAF-20C	KPU19	<b>060L2150</b> <sup>1</sup>
KPU 19			SPST/Auto	80	140	A19AAD-5C A19ABA-40C A19AAD-12C		
KPU 19	Room bulb	-30 to 80	SPDT/Auto	Room sensor	140	A19BBC-2C A19BAB-3C A19BAC-1C A19BAF-1C	KPU19	<b>060L2152</b>

<sup>1</sup> As 060L1250 is SPDT, 060L2150 can replace competitor parts crossed to both 060L2150 and 060L2151.

Contact Load	Resistive load		0.5~16A/120V AC 0.5~8A/240V AC
	Inductive load	Full load	0.5~16A/120V AC 0.5~8A/240V AC
		Locked rotor	96A/120V AC 48A/240V AC
	Pilot duty		125VA/240V DC



Scan the QR Code for a video of a KPU 19 temperature control replacement or visit [http://bit.ly/KPU19\\_video](http://bit.ly/KPU19_video)