Innovative Products





RUGGED, RELIABLE & IMPACT RESISTANT...

Start Strong with PolarPad

Condenser installations begin better with PolarPad. The PolarPad is a plastic pad engineered and designed as a base for HVAC equipment. The pad is injection molded from polyethylene, which is durable, strong, and lightweight. The unique design has strong, uniform ribbing along the underside. The pad is molded with a texture along the top for traction, and rounded edges on the sides to give a clean concrete look and feel.



Unparalleled Durability, Perfectly Level, and 90% Lighter Than Concrete Pads... and That's Just the Tip of the Iceberg.

MARS Disconnect Boxes



| MARS No. | Description | Top/Side Open | Value/Basic/ Premium | |
|-------------|-------------------------------|------------------|-------------------------|--|
| 80301 | Low Profile 60 Amp, Non-Fused | Side Open | Value | |
| 83615 | 60 Amp, Non-Fused | Top Open | Value | |
| 83616 | 30 Amp, Fused | Top Open | Value | |
| 83617 | 60 Amp, Fused | Top Open | Value | |
| 83315 | 60 Amp, Non-Fused | Top Open | Basic | |
| 83316 | 30 Amp, Fused | Top Open | Basic | |
| 83317 | 60 Amp, Fused | Top Open | Basic | |
| 83396 | Compact 30 Amp, Fused | Top Open | Basic | |
| 80315 | 60 Amp, Non-Fused | Side Open | Premium | |
| 80316 | 30 Amp, Fused | Side Open | Premium | |
| 80317 | 60 Amp, Fused | Side Open | Premium | |

MARS Bulk Packaged

A/C Whips, Non-Metallic Fittings

- · Packaged gaylord style
- · Bulk box for easy access





| MARS No. | | Description | MARS Pack |
|-------------|-----------|------------------------------|--------------|
| 84181 | 4' x 1/2" | #10 ga. non-metallic whip UL | 90 |
| 84183 | 4' x 3/4" | #8 ga. non-metallic whip UL | 60 |
| 84185 | 6' x 1/2" | #10 ga. non-metallic whip UL | 60 |
| 84187 | 6' x 3/4" | #8 ga. non-metallic whip UL | 45 |



7 MOTORS = ALL JOBS SOLVED

Variable Speed ECM 2 Motors Replace Most Any OEM

Azure connects directly to OEM harnesses



4 Pin Variable Speed



16 Pin Variable Speed

Replaces 16 Pin OEM Variable Speed ECM, PWM, 2.0, 2.3, 2.5 EON®; and Evergreen® VS. Rescue® EZ16®

Replaces Many* 4 Pin **OEM Variable Speed** ECM 3.0; and Evergreen® VS





Bluetooth inside

Smartphone not included

| MARS No. | HP | Volts | RPM | Rotation | Diameter |
|-------------|---------|---------|---------------|----------|----------|
| 10856 | 1/4-1/2 | 115/230 | 1075 Variable | REV | 5.5" |
| 10857 | 1/2-1 | 115/230 | 1075 Variable | REV | 5.5" |

*Due to proprietary OEM protocol, some communicating ECMs may not be compatible with Azure.

2 Motors Replace Any Constant Torque ECM

One Touch Autosizing

One touch of a button automatically assigns torque for the ductwork

Individual Speed Tap Adjustments

Dial in the temperature rise with 1% torque increments. Tune out annoying high frequency harmonics. Optimize CFM

Real Time Data

Monitor motor volts, amps, watts, and RPM's

Drop-in Installation

Simple to wire; connects directly to all factory OEM harnesses

| MARS No. | НР | Voltage | Rotation | OEM Constant Torque Application |
|-------------|-----------|---------|----------|--|
| 10858 | 1/5 – 1/2 | 115/230 | REV | X13 [®] , Ensite [®] , Endura [®] , Digi-Motor [®] , SelecTech [®] |
| 10859 | 1/2 – 1 | 115/230 | REV | X13 [®] , Ensite [®] , Endura [®] , Digi-Motor [®] , SelecTech [®] |

2 Motors Replace ANY PSC **Blower Motor**

Drop-In ECM Direct Drive Replaces Standard PSC Motors

Dedicated 625RPM Speed Tap

Ideal for IAQ equipment

Constant Torque Design

Improves airflow

Simple Line Voltage Speed Taps

Wires like the PSC motor it replaces

Ultimate Truck Stock Motor

Saves time and money



| MARS No. | Dia. | НР | Volts | Speeds | Rotation | Includes Quickswap [®] Board |
|-------------|------|---------|---------|--------|----------|---|
| 10865 | 5.5" | 1/3-1/2 | 115/230 | 5* | REV | NO |
| 10866 | 5.5" | 3/4-1 | 115/230 | 5* | REV | NO |

One Motor Replaces Most PSC Condenser Fan Motors

825 & 1075 RPM Motor in One

Easy to Mount

The short shell 1/3 HP fits where larger competitive motors will not

Easy to Configure

Simply power the motor to cycle it through 4 possible configurations and lock in the desired mode;

1075 RPM CW • 1075 RPM CCW 825 RPM CW • 825 RPM CCW

Simple 2 Wire Installation

Connect the 2 motor leads directly to the definite purpose contactor; there are no capacitor, rotation, or RPM jumper wires

Outboard Surge Protection

Unique to Azure® is the replaceable outboard surge protector included within the wire harness of each Azure® condenser fan motor



| MARS No. | НР | Volts | RPM | Rotation | Orientation | Rheem Holes |
|-------------|-----------|---------|----------|----------|-------------|----------------|
| 10874 | 1/8 – 1/3 | 208-230 | 825/1075 | REV | Shaft Down | Yes |

Capacitor SuperStore

AMRAD USA MADE CAPACITORS

Over 80 years of quality, reliability and durability

- 5 Year Warranty
- Made in the USA
- Rust free all brass terminals
- The ONLY motor-run capacitors with CPT®



Turbo Universal

Capacitors



- Truly Universal –
 Replace over
 200 Capacitors
- Made in the USA
- Non-PCB dielectric fluid to reduce heat
- Compressor
 Protector Terminal
- 5 Year Warranty



MARS USA

Capacitors



- Made in USA
- OEM Grade
- Meets EIA-456A
 Test Standard
- Patented dielectric fluid & premium metalized film
- 5 Year Warranty



MARS Blue Box

Capacitors



- Made in North America
- OEM Grade
- Meets EIA-456A Test Standard
- Patented dielectric fluid & premium metalized film
- 2 Year Warranty

JARD

Capacitors



- · Made in North America
- Aftermarket Grade
- 1 Year Warranty

Unmatched comfort, unbelievably economical.



Introducing the new SE Series.















MULTI-POSITION AIR HANDLER

VCD-Series



Extreme Performance Cold Weather Heat Pump

Up to 18.0 SEER2

Six models to choose from 18,000 to 60,000 BTUH

Operating range:

Cooling

5°F (-30°C) - 122°F (50°C)

-22°F (-30°C) - 75°F (24°C)



Features

- · Accepts traditional 24VAC thermostats for convenience and advanced control options
- · Wired programmable control included
- · Optional electric resistance heat kits
- · Multi-position air handler



